P344

Smart 12MP PoE Dome Camera with Powerful Spotlight



#### 12MP UHD

Capture intricate details from facial features to license plates.



#### **Two-Way Audio**

Speak directly to anyone who approaches your home.



#### Weatherproof

Rated as IP67 to withstand the elements for year-round protection.



#### **Color Night Vision**

See through the night in full color with its spotlight on.



#### Power over Ethernet

Get both power & data with a single network cable.



### 24/7 Recording

Work with Reolink NVRs to save days of your 24/7 footage.



## Smart Detection & Alerts

Get instant notifications once a person, vehicle or animal is detected.



#### **Remote Access**

Access your live feed anytime anywhere via Reolink App/ Client.



#### Customized Motion Zone

Map out your detection to only get alerts about specific areas.

reolink




#### Next-Level Clarity in 12MP

Home security has entered the 12MP era. Get a clear and detailed view of your home, and see everything with incredible clarity.



#### Focus on True Threats

Differentiate people, vehicles, and animals from other objects and send alerts straight to your phone, so nothing important goes unnoticed.




#### Talk Like You're There

The built-in mic and speaker allow you to communicate clearly with arriving guests or deter intruders with a "Get Away" message.



### See Through the Night in Colors

Fuzzy and pixelated night vision is now history. The powerful spotlight that keeps on all night makes the night as colorful as day.



#### **PoE, Setup in Minutes**

Transmit videos and be charged simultaneously via only one network cable. Setup is easier with no messy cables.

#### Gallery




Stay connected to your home or business anytime, anywhere.



We made it a priority to ensure that your privacy is protected and your data is for your eyes only.



Model	P344	
Video & Audio	Image Sensor	1/2.49" CMOS Sensor
	Video Resolution	Default: 4512X2512 (12 megapixels) at 20 frames/sec
	Lens	f=4.0mm; F=1.6, with IR-cut filter
	Video Format	H.265
	Field of View	Horizontal: 97°
		Vertical: 50.6°
	Day & Night	Auto-switching with IR-cut filter
	Infrared Night Vision	30 meters (LED: 2pcs/28mil/850nm)
	Color Night Vision	Spotlight: 1pcs/4.3W/6500K/700 Lumens
	Audio	Two-way audio (via Reolink App/Client)
Power	РоЕ	IEEE 802.3af, 48V Active
Requirements	DC Power	DC 12.0V=1A, <12W
Interface	Power	DC power port
	System	Reset button
	Ethernet	One 10M/100Mbps; RJ45
	Audio	Built-in microphone and speaker
Software Features	Frame Rate	Mainstream: 2fps - 20fps (default: 20fps)
		Substream: 4/ 7/ 10/ 15/ 20fps (default: 10fps)
	Code Rate	Mainstream: 3072Kbps - 10240Kbps (default: 8192Kbps)
		Substream: 128Kbps - 1024Kbps (default: 768Kbps)
	Smart Alarm	Motion detection; person detection; vehicle detection; animal detection
	Record Mode	Motion-triggered recording (default); scheduled recording; 24/7 recording
Working Environment	Temperature	Operating temperature: -10°C~+55°C (14°F~131°F)
	Humidity	Operating humidity: 10% ~ 90%
	Weatherproof	IP67
Size & Weight	Dimension	117.4 x 103.7mm
	Weight	510g
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/.



#### **Best Companion**



PoE Injector



Reolink NVR



Ethernet Cable



Waterproof Lid



Junction Box D20

### **Download Free Reolink App & Client**

Learn more: <u>https://reolink.com/software-and-manual/</u>



#### **Terms and Privacy**

Terms and Privacy: Use of the product is subject to your agreement to the Terms of Service and Privacy Policy at reolink.com. Keep out of reach of children.

#### **Limited Warranty**

Limited Warranty: This product comes with a 2-year limited warranty. Learn more: https://reolink. com/warranty-and-return/

### NVS8

8-Channel PoE NVR for 24/7 Reliable Recording



#### 8-Channel

The NVR can connect up to 8 Reolink PoE/WiFi cameras.

## **16MP**

#### Support up to 16MP

Record up to 16MP ultra-clear videos on every channel.



#### ΡοΕ

The plug-and-play setup saves you time and effort.



#### **Built-in 2TB HDD**

reølink

Store videos locally on a pre-installed 2TB HDD (upgradable to 12TB).

## 0000

#### **All-Around Protection**

Stand guard over every inch of your property with up to 8 cameras.



#### **Remote Access**

Easily check live feeds from anywhere via the Reolink App/Client.



#### 24/7 Recording

Continuous recordings directly to your hard drive with expandable storage.



#### **Centralized Security**

Take full control of all cameras with centralized NVR management.



#### **Local Access**

Access the live feeds offline via a monitor or an HD TV.



#### **Centralize Your Security**

Connect your Reolink cameras to the NVR for centralized management, all-round surveillance, and more. Everything is under your control.



#### 24/7 Continuous Recording

Save days of your 24/7 footage securely and locally on a 2TB HDD (upgradable to 12TB). Never worry about data loss.




#### Your Personalized Security Solution

The 8-Channel NVR is compatible with all our IP cameras up to 16MP PoE/WiFi cameras. Have fun customizing your own security system.



#### **PoE - Easy Setup**

Simply connect your cameras to the NVR with a network cable for both data & power transmission. No messy cables, ideal for DIY lovers.



#### Local and Remote Access & Control

Access the live streams of all cameras anywhere with the Reolink App/Client, or connect the NVR to a monitor for local monitoring.

#### Gallery



### One App/Client for All Control

Stay connected to your home or business anytime, anywhere.




#### **Privacy in Your Hands**

We made it a priority to ensure that your privacy is protected and your data is for your eyes only.



Model	NVS8	
Hardware	Hardware	N7MB01
Video/Audio Input	IP Video Input Audio Input	PoE IP Camera x 8 Cameras with built-in mic
Video/Audio Output	HDMI Output Resolution	3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768
	VGA Output Resolution Audio output	1920x1080, 1280x1024, 1280x720, 1024x768 1-Channel, RCA
Decoding	Video Format	H.264, H.265
	Live View / Playback Resolution	7680×2160, 4608×1728, 4512×2512, 4096×3072, 3840×2160, 2560×256 2560×1920, 2560×1440, 2048×1536, 2304×1296, 1080p, 720p
	Synchronous Playback	Up to 4 channels
HDD	SATA	1 x SATA interface (1 x 2TB HDD included)
	External HDD	1 eSATA Interface for HDD
	Capacity	Up to 12TB (max. 6TB capacity for each HDD)
External Interface	USB Interface	2 x USB 2.0
	Network Interface	1, RJ-45 10/100 Mbps self-adaptive Ethernet interface for LAN/ WAN
		8, RJ-45 10/100 Mbps self-adaptive PoE Ethernet interface for IP camera
PoE	Max. Power Per Port	25W
	Supported Standard	IEEE 802.3af/at
Network	Network Protocols	HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP
	Browsers Supported	Edge, Firefox, Chrome, Safari
	OS Supported	PC: Windows, Mac OS; smartphone: iOS, Android
	Max. User Access	20 users (1 admin account & 19 user accounts); supports up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
General	Power Supply	DC 48V~53V
	Power Consumption	<10W (Without HDD&PoE)
	Working Environment	Temperature: -10°C~+45°C (14°F~113°F); humidity: 10%~90%
	Dimensions	260 x 41 x 230mm
	Weight	1.4kg
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/.





#### **Best Companion**



Mouse

#### **Download Free Reolink App & Client**

Learn more: <u>https://reolink.com/software-and-manual/</u>



#### **Terms and Privacy**

Terms and Privacy: Use of the product is subject to your agreement to the Terms of Service and Privacy Policy at reolink.com. Keep out of reach of children.

#### **Limited Warranty**

Limited Warranty: This product comes with a 2-year limited warranty. Learn more: https://reolink. com/warranty-and-return/